


# RioTouch Dong Guan RioTouch Technology Co., Ltd

Room 203, Building 1, No.1 Chang Qing South Road, Chang An Town, Dongguan City

Web: [www.RioTouch.com](http://www.RioTouch.com)

## OPS I3 10100 16+256GB SSD

<b>Model</b>	<b>I3 10100 16+256GB SSD</b>	
<b>Product Picture</b>	 <div style="display: flex; justify-content: flex-end; gap: 10px; margin-top: 10px;"> <div style="border: 1px solid black; padding: 2px 5px; font-size: 8px;">intel</div> <div style="border: 1px solid black; padding: 2px 5px; font-size: 8px;">4K 60Hz</div> <div style="border: 1px solid black; padding: 2px 5px; font-size: 8px;">M.2</div> <div style="border: 1px solid black; padding: 2px 5px; font-size: 8px;">USB 3.2</div> <div style="border: 1px solid black; padding: 2px 5px; font-size: 8px;">Type-C</div> </div>	
<b>Product features</b>		
	<p>Comet Lake-S 10th 11th Gen Intel ® CoRE™ I3 processor            Display has HDMI, DP and supports synchronous/asynchronous dual display            Compatible with OPS-C full series product upgrading and switching            Support dual channel SO-DIMM DDR4 memory and M 2 SSD storage            BIOS supports AMI 64Mbit diskless startup, power on and timing startup            Support JAE 80PIN connection interface            Support TPM2.0</p>	
<b>Specifications</b>		
<b>Standard</b>	CPU: 10th 11th Gen Intel®Core™ I3 processor	
	Memory: 2 X SO-DIMM DDR4 2400/2666MHz 4GB memory	
	Storage: 1*M. 2 2280 interface supports NVME and SATA dual protocols (SSD128G) 1* 2.5" SATA HDD/SDD	
	GPU: Intel® UHD Graphics for 10th 11th Gen	
	Display Output: HDMI/DP supports synchronous and asynchronous dual display	
	Internet: LAN Intel I219 Gigabit Ethernet WIFI 1*M.2 2230 for Wifi+BT	
	Audio: Realtek ALC897 audio 5.1 channel	
<b>I/O ports</b>	Front interface: 1*HDMI out / 1*DP out / 5*USB3.0 / 1*USB2.0 / 1* RJ45 / 1*Power / 1* Reset / 1*Line out / 1*Mic in / 1 * Type-C (supporting video transmission+USB3.0 transmission) / 1*Power LED / 1*HDD/SSD LED / 2*WIFI/BT ANT	
	Rear interface:1*JAE 80PIN: HDMI2.0 out(4K/60Hz)	
<b>Power</b>	Power input: 119V 4.7A	
<b>Dimension</b>	Host size (mm): Bare machine: 195*180*42, Packing box size: 282 * 257 * 79mm	
	Weight (kg) : Net weight ≈ 1.2 KGS, Gross weight ≈ 1.4 KGS	
<b>Temperature and humidity</b>	working temperature: 0°C~ 45°C	
	Storage temperature: -40°C~ 80°C	
	Operating humidity: 10% - 95% @ 40 ° C non condensing	
<b>System</b>	Operating system support: Windows 8/10/11, Linux	
<b>Ordering information</b>		
<b>Comet Lake-S 10/11 processor</b>	I3-10100	
<b>DDR4 memory/RAM</b>	16G	
<b>Hardish/SSD</b>	SSD 256G	